


Technical Data Sheet

Last data update


5/9/2019

9010
novantadieci®




Req. space behind the plasterboard

30mm




hole on the plasterboard

140x140mm




External measures

135x135mm



Measures of the light output

Ø30mm



Height without electrical part

13mm



Height including the electrical part

25mm

Notes on measures

General notes

CEILING RECESSED LIGHTING

4248E-30150

Recessed Spotlight / CRISTALY

Surface finish : CRISTALY

LED 4W / 200mA / 450lm / 3000°K / CRI90

Model

Code	4248E
Product family	CEILING RECESSED LIGHTING
Type	Recessed Spotlight

Material/Surface finish

Code	004
Material	CRISTALY
Surface finish	CRISTALY

Electrical part

Code	30150
Type	LED
Power	4W
Current	200mA
Light Output	450lm
Colour Temperature	3000°K
CRI	90

Light Output of the lamp	270lm
Dimmable	SI

Power Supply	by Remote Power Supply
Connection	Screw Terminal
Cover	LENTE IN VETRO

General Data

Protection Index	IP20/IP44
Isolation Class	III
Weight [Kg]	0.6
Country of production	MADE IN ITALY
Mounting instruction	025.599_9010

Installation

Multisize system	NO
Position	Ceiling

Packaging


Type	White die-cut Box
Measures AxBxH	245x165x65mm
Gross Weight [Kg]	0.6539
Master carton	NO
Quantity of articles	
Measures AxBxH	

Technical Data Sheet

4248E-30150

9010
novantadieci®

Fotometric Data




<i>Electrical part</i>	30150
<i>Power</i>	4W
<i>Light Output</i>	450lm
<i>Colour Temperature</i>	3000°K
<i>CRI</i>	90
<i>Lamp Light Output</i>	60%
<i>Light Output of the lamp</i>	270lm
<i>Beam Angle</i>	60°
<i>Beam Inclination</i>	

<i>Illuminance</i>	1m	266lux
	2m	67lux
	3m	30lux
	4m	17lux
	5m	11lux

Accessories

Housing Box for Brickwork



<i>Code</i>	023.4010
<i>Measures</i>	235X140X45mm
<i>Measures of the hol</i>	265X170X55mm

Standard Power Supply



<i>Code</i>	026.218
<i>Measures</i>	75x38x22mm
<i>Power</i>	8W
<i>Input</i>	220-240 V~
<i>Output</i>	200mA

Dimmable Power Supply



<i>Code</i>	026.300
<i>Measures</i>	155x51x26mm
<i>Power</i>	9.2W
<i>Input</i>	220-240V~
<i>Output</i>	200mA
<i>Dimmable</i>	PUSH/0-10V/DALI


Technical Data Sheet

4248E-30150

9010
novantadieci®

Accessories

Other Accessories



<i>Code</i>	099.142
<i>Description</i>	Emergency Kit
<i>Notes</i>	