



**VACUUM  
TRAY SEALER**



The logo for ORVED features the word "ORVED" in a bold, white, sans-serif font. The text is centered within a white, stylized swoosh that curves around the top and bottom of the letters, resembling a protective lid or a dynamic motion line.

**ORVED**

Sustainable  
*Progress*  
future *for* all

The ideal tray packaging solution for all product types, including ready-to-serve meals. Versatile in tray size and design, with a steadfast focus on food wellness, innovation, and sustainability.





**VGP 60**  
MADE IN ITALY







Protect, preserve,  
enhance  
*freshness*

# Versatility and cleanliness




**VGP 60**  
MADE IN ITALY



The unmatched  
essence  
*of being*

# VGP Collection





### **CUSTOMIZABLE MOLDS**

Engineered to fit products of any shape and size, ensuring maximum flexibility and flawless sealing.



### **QUICK GAS CONNECTOR**

Rapid-lock system for effortless inert gas connection, optimizing workflow efficiency.



### **TOUCH SCREEN (VGP60 AND VGP PRO)**

The touch control system simplifies operation and enables instant selection of the ideal process for optimal packaging, even for inexperienced users.



### **INTEGRATED WIFI (VGP12 MINI & VGP25)**

Connect to your corporate network to access advanced features: packaging data downloads, software updates, program loading, maintenance history, and remote display intervention.



### **INTEGRATED COMPRESSOR (VGP25, VGP60 & VGP PRO)**

Built directly into the machine, eliminating external devices for greater convenience, space savings, and consistent performance.



### **SENSORIAL VACUUM SYSTEM**

Guarantees perfect, consistent vacuum levels, adjusting packaging times based on product dimensions and humidity








### **OXYGEN CONFIGURATION** (OPTIONAL FOR VGP 25-60-PRO)

Certified system for gas mixtures with >21% oxygen, ideal for MAP packaging of fresh meat



### **CUT OF SEAL SOLUTION** (EXCEPT VGP 12)

Excess tray material is trimmed post-sealing for pristine refrigerator-ready packaging and optimal retail presentation



### **EASY TO MOVE** (EXCEPT VGP 12)

Swivel-wheel models ensure adaptable mobility for production needs.



### **ERGONOMIC HANDLE**

Il sistema di chiusura facilitato riduce lo sforzo fisico e l'affaticamento degli operatori, rendendo la chiusura del coperchio semplice. Ideale per lavorazioni continuative.



### **3 PACKAGING MODES**

VGP machines support vacuum sealing, modified atmosphere (MAP), or simple heat sealing.




### **DEGAS** (VGP 60 & PRO)

Customizable progressive vacuum processes with ramp/step sequencing for standardized, high-quality deaeration.




## VGP 60 - VGP PRO CONFIGURATIONS

UNIVERSAL SEALING PLATE



CUT OF SEAL COMPLETE SEALING GROUP (OPTIONAL)



- SENSORIAL VACUUM SYSTEM**
- VACUUM + GAS (MAP)**
- 10 USER PROGRAMS**
- TOUCH PANEL**
- CUSTOMIZABLE DEGAS PROCESS**
- BOOSTER COMPRESSOR**
- SELF-BRAKING FILM ROLL SYSTEM**

**OPTIONAL**

- CUT OF SEAL**
- OXYGEN CONFIGURATION (BOOSTER COMPRESSOR NOT INCLUDED WITH THIS OPTION)**

**STANDARD MOULD / CUT OF SEAL COMPLETE SEALING GROUP**

**POLYPROPYLENE**

- 1X 1/2 GASTRONORM**
- 2X 1/4 GASTRONORM**
- 4X 1/8 GASTRONORM**

**COMPOSTABLE**

- 2X 227X176XMM O 187X139XMM**
- 4X 145X105XMM**

**CPET**

- 1X 260X160X50MM**
- 2X 190X136X50MM**
- 4X 120X136X45MM**

**CUSTOM MOLDS (ON REQUEST)**


| MODEL   | DIMENSIONS    | WEIGHT | VACUUM PUMP | POWER SUPPLY           | MAX TRAY DIMENSIONS | PACKAGING METHODS                     |
|---------|---------------|--------|-------------|------------------------|---------------------|---------------------------------------|
|         | mm (LxIxh)    | kg     | mc/h        | V / Hz / W             | mm                  |                                       |
| VGP 60  | 497x746x1158h | 155    | DVP 60      | 400 / 50-60 3ph / 2900 | 325x260x120h        | Seal Only / Vacuum / Vacuum+Gas (MAP) |
| VGP PRO |               | 135    | BUSCH 20    | 220/240 / 50-60 / 900  |                     |                                       |






## VGP 25 CONFIGURATIONS

UNIVERSAL SEALING PLATE



CUT OF SEAL COMPLETE SEALING GROUP (OPTIONAL)



-  SENSORIAL VACUUM SYSTEM
-  VACUUM + GAS (MAP)
-  10 USER PROGRAMS
-  PANNELLO DIGITALE
-  BOOSTER COMPRESSOR
-  SELF-BRAKING FILM ROLL SYSTEM

OPTIONAL



-  WIFI
-  CUT OF SEAL
-  OXYGEN CONFIGURATION (BOOSTER COMPRESSOR NOT INCLUDED WITH THIS OPTION)

STANDARD MOULD / CUT OF SEAL COMPLETE SEALING GROUP




POLYPROPYLENE

-  1X 1/2 GASTRONORM
-  2X 1/4 GASTRONORM
-  4X 1/8 GASTRONORM

COMPOSTABLE

-  2X 227X176XMM O 187X139XMM
-  4X 145X105XMM

CPET

-  1X 260X160X50MM
-  2X 190X136X50MM
-  4X 120X136X45MM


CUSTOM MOLDS (ON REQUEST)

| MODEL  | DIMENSIONS    | WEIGHT | VACUUM PUMP | POWER SUPPLY           | MAX TRAY DIMENSIONS | PACKAGING METHODS                     |
|--------|---------------|--------|-------------|------------------------|---------------------|---------------------------------------|
|        | mm (LxIxh)    | kg     | mc/h        | V / Hz / W             | mm                  |                                       |
| VGP 25 | 497x746x1158h | 131    | DVP 25      | 220-240 / 50-60 / 2850 | 325x260x120h        | Seal Only / Vacuum / Vacuum+Gas (MAP) |




## VGP 12 MINI

TESTATA SALDANTE  
UNIVERSALE



 **SENSORIAL  
VACUUM  
SYSTEM**

 **VACUUM +  
GAS (MAP)**

 **20 PROGRAMMI  
UTENTE**

 **PANNELLO  
DIGITALE**

OPTIONAL

 **WIFI**

STAMPO STANDARD

POLYPROPYLENE

1X 260X160X50 MM

2X 165X120X45 MM

COMPOSTABILE

1X 227X176X50 MM O 227X176X44 MM

2X 227X176XMM O 187X139X MM

2X 145X105X MM

CPET

1X 260X160X50 MM

2X 190X136X50 MM

2X 120X136X45 MM

| MODEL       | DIMENSIONS   | WEIGHT | VACUUM PUMP | POWER SUPPLY       | MAX TRAY DIMENSIONS | PACKAGING METHODS                     |
|-------------|--------------|--------|-------------|--------------------|---------------------|---------------------------------------|
|             | mm (LxIxh)   | kg     | mc/h        | V / Hz / W         | mm                  |                                       |
| VGP 12 mini | 391x759x734h | 60     | DVP 12      | 230 / 50-60 / 1850 | 190x260x50h         | Seal Only / Vacuum / Vacuum+Gas (MAP) |

Your products  
*never* this  
perfectly *shaped*





Shape your  
products with  
precision





### SKIN GAS TECHNOLOGY

small quantity of gas injection preserves the 'second skin' effect while preventing film punctures from sharp-edged products.



### SENSORIAL VACUUM SYSTEM

Guarantees perfect, consistent vacuum levels, adjusting packaging times based on product dimensions and humidity




### EASY TO MOVE (EXCEPT VGP12)

Swivel-wheel models ensure adaptable mobility for production needs.

# [5]

### 5 PACKAGING MODES (COMBI SKIN ONLY)

Skin, Skin+Gas, Vacuum, MAP, Seal Only – Adapt to every need.



### INTERCHANGEABLE MOULDS

Easy sealing group replacement system. All models include suction holes to easily hold the film in a perfect position for subsequent packing.




### QUICK GAS CONNECTOR

Rapid-lock system enables simple, instant inert gas connection.



# VGP SKIN

1 SKIN SEALING GROUP AT YOUR CHOICE



SENSORIAL VACUUM SYSTEM



VACUUM + GAS (MAP)



USER PROGRAMS



TOUCH PANEL



SELF-BRAKING FILM ROLL SYSTEM

OPTIONAL



ADDITIONAL SKIN SEALING GROUP



KIT SKIN

STANDARD SKIN MOULD



1X B6



1X D15



2X D2



2X B5




2X D13

| MODEL       | DIMENSIONS    | WEIGHT | VACUUM PUMP | POWER SUPPLY           | MAX TRAY DIMENSIONS | PACKAGING METHODS                       |
|-------------|---------------|--------|-------------|------------------------|---------------------|---|
|             | mm (LxIxh)    | kg     | mc/h        | V / Hz / W             | mm                  |   |
| VGP 60 SKIN | 497x746x1158h | 178    | DVP 60      | 400 / 50-60 3ph / 2900 | 190x260x50h         | Skin Vacuum / Skin Gas / Simple sealing |




## VGP COMBI SKIN CONFIGURATIONS

TESTATA SKIN  
A SCELTA




+

TESTATA SALDANTE  
UNIVERSALE



TESTATA SOLUZIONE  
PER TAGLIO SFRIDO (OPTIONAL)



- SENSORIAL VACUUM SYSTEM
- VACUUM + GAS (MAP)
- VUOTO GAS (ATM)
- USER PROGRAMS
- TOUCH PANEL
- SELF-BRAKING FILM ROLL SYSTEM

OPTIONAL

- CUT OF SEAL
- ADDITIONAL SKIN SEALING GROUP
- KIT SKIN

STANDARD MOULD / CUT OF SEAL COMPLETE SEALING GROUP

STANDARD SKIN MOULD

1X B6 - D15

2X B5 - D2 - D15

POLYPROPYLENE

1X 1/2 GASTRONORM

2X 1/4 GASTRONORM

4X 1/8 GASTRONORM

COMPOSTABLE

2X 227X176XMM O 187X139X MM

4X 145X105X MM

CPET

1X 260X160X50 MM

2X 190X136X50 MM

4X 120X136X45 MM


CUSTOM MOLDS (ON REQUEST)

| MODEL          | DIMENSIONS    | WEIGHT | VACUUM PUMP | POWER SUPPLY           | MAX TRAY DIMENSIONS | PACKAGING METHODS   |
|----------------|---------------|--------|-------------|------------------------|---------------------|---|
|                | mm (LxIxh)    | kg     | mc/h        | V / Hz / W             | mm                  |   |
| VGP COMBI SKIN | 497x746x1158h | 178    | DVP 60      | 400 / 50-60 3ph / 2900 | 190x260x50h         | Skin Vacuum / Skin Gas / Simple sealing/ Vacuum/ Vacuum MAP |

# PROFI Collection








### **CUSTOMIZABLE MOLDS**

Engineered to fit products of any shape and size for maximum flexibility and flawless sealing.



### **AUTOMATIC FILM CUTTER**

Cuts film post-sealing for easy tray removal and production efficiency.



### **HIGH-SPEED PACKAGING**

Uniform edge sealing in seconds. Ideal for supermarkets, delis, and takeaway.



### **DIGITAL PANEL**

User-friendly thermostat for optimal packaging results, even for beginners.



### **WORK TOP**

Molds are designed to ensure perfect tray placement for even, secure, and durable seals.



### **FIXED WORKTOP (NO LIQUID LEAKS)**

Prevents spills of sauces, oils, or liquids during tray placement.



## PROFI 3

### STAMPI STANDARD POLYPROPYLENE

- 1X 1/2 GASTRONORM
- 2X 1/4 GASTRONORM
- 4X 1/8 GASTRONORM

### CUSTOM MOLDS (ON REQUEST)

| MODEL   | DIMENSIONS   | WEIGHT | POWER SUPPLY           | STANDARD MOULDS                      |
|---------|--------------|--------|------------------------|--------------------------------------|
|         | mm (Lxhx)    | kg     | V / Hz / W             | mm                                   |
| Profi 3 | 330x590x410h | 23,5   | 220-240 / 50-60 / 1650 | 4x 116x163 / 2x 257x156 / 1x 325x260 |



**PROFI 2**



**PROFI 1N**

**STAMPI STANDARD POLYPROPYLENE**

- 1X 160X290 MM
- 2X 140X190 MM + 140X90 MM

**STAMPI STANDARD COMPOSTABLE**

- 1X 227X176 MM
- 2X 145X105X43 MM / 2X 187X139X45 MM

**STAMPI STANDARD PET**

- 1X 260X190 MM
- 2X 190X136 MM / 2X 120X136 MM

**CUSTOM MOLDS (ON REQUEST)**

- 1X 140X190 MM / 1 X140X90 MM

| MODEL    | DIMENSIONS   | WEIGHT | POWER SUPPLY          | STANDARD MOULDS                     |
|----------|--------------|--------|-----------------------|-------------------------------------|
|          | mm (LxIxh)   | kg     | V / Hz / W            | mm                                  |
| Profi 1n | 221x447x326h | 14     | 220-240 / 50-60 / 340 | 1x 137x190 / 1x 137x95              |
| Profi 2  | 260x530x340h | 16,5   | 220-240 / 50-60 / 750 | 1x 137x190 / 1x 95x137 / 1x 189x260 |

# Orved Control

The app for managing your laboratory.

Inventory control, Product expiry monitoring, customizable label templates.





# TAG Printer

- Print labels for all your products
- Labels are heat- and water-resistant, usable in blast chiller, fridge, or freezer
- Automatically set the shelf life to have an expiration date
- With the dedicated app, you can keep track of your inventory
- The app allows you to view products nearing expiration or already expired




# All the assistance you need



**ORVED**  
**NEXUS**

# Learn more

scan with your smartphone




**External Extraction**

---



**Accessories**

---



**Services**

---



**Orved S.p.A.**

Via dell'Artigianato, 30  
30024 Musile di Piave (VE)

tel:+39.0421.54387  
orved@orved.com



Company with quality management system  
certified by DNV ISO 9001.



[www.orved.com](http://www.orved.com)