



Ortelli
Technologies

MVS2proDENSITY

Resolve your density measurement with performance




**The Automatic Determination
of the Volumic Mass**
RELIABLE, REPRODUCIBLE, OBJECTIVE, CERTIFIABLE



ISO 9001
BUREAU VERITAS
Certification







Data Sheet



MVS2pro is a robotized system for the determination of the Density or the Standard Absolute Volumic Mass (MVS) of polymers by the principle of the Hydrostatic Push opportunely corrected in order to obtain the result expressed in the MV (S) unit.

MVS2pro determines the Volumic Mass in a completely automated cycle that replaces the old system used for this measure (Gradient Columns), that was characterized by typical human errors.

MVS2pro System is perfectly integrated in the quality Standard Process **ISO9001**.

It's already supported by all the control procedures for the carried out measures using two different kinds of Standard:

- 1 certified Density Standard
- 1 standard Temperature (certificated thermometer)

All integrated in a statistical plan of controls to check the validity of the analytical determinations of the samples.

MVS2pro has an Autosampler with a maximum of 16 samples and/or Standard of Density or Volume.

The system makes the measure of a sample in less than 5 min.

MVS2pro constantly controls the Temperature to which it comes carried out the measure to have the certainty that will be respected the range of working set in the method. This **Pt100 probe** can be calibrated using the procedure from the management software with a primary Standard.

MVS2pro was born for the determination of MVS on **High Density Polyethylene (HDPE)** but it is obviously usable for the same kind of determination with other kind of materials can be analyzed with the method of the hydrostatic push.

Integral contro I of the **MVS2pro** system takes place via LAN from a software console (included in the price) that is installed on a PC in the corporate network (or, if necessary, with a direct connection to the PC). The software console allows you to control the system and keeps DB archive of all historical data and all the measurements made to obtain it. It is possible to re-calculate archived data with other types of applications like Excel, Access and transfer them directly to LIMS.



Technical Data

- **Model:** MVS2pro
- **Reproducibility:** < 0.05%
- **Range of Temperature:** from 10°C to 50°C (usually 23°C)
- **Medium Time of Analysis:** 5 min/sample
- **Sample dimensions:** diam. approx 40 mm, thin approx. 20 mm
- **Autosampler:** 16 or 25 samples
- **The System MVS2pro is compliant to the ISO1183-1, ISO2781 and ISO 293 for sample preparation.**



Accessories (required)

Support samples series hook and helicoid form



Set of 20 hook shaped support samples.

The kit is composed in this way: in 4 different colours: gold, green, red and blue, 16 hook/helicoid form, 2 helicoid/hook form and 2 basket supports.



[Watch the Video!](#)

Basket Support samples



The kit is composed in this way: 16 basket supports, 2 helicoid supports, 2 hook supports.
In the perforated basket support you can include some polyethylene spheres or other material like fragments of glass or precious stones (diamonds).

[Watch the Video!](#)



Mettler Analytical Balance



Analytical Electronic Balance with underplane support weight to position the support sample in the measurement area of the **MVS2pro**. The balance suggested is at 5 decimal places in grams like: MS, XSR, XPR Series. ($d=0,01$ mg)
The Balance is directly controlled by **MVS2pro** via USB.

Glass Cover Wind Protection Assy



Device perfectly compatible with the MVS2pro system allows to protect the balance from interference for example air displacements inside the laboratory, allowing a better stabilization of the balance.

Thermostatic Bath



System of thermostatisation for the beaker (beaker thermostatable).

It allows the maintenance of the liquid measurement at the temperature described in the method.

The system has a suction pump to recirculate the thermostated liquid in an external circuit.

The system is directly controlled by MVS2pro via USB.

Certified Density Standard

Certified Density Standard in Glass.



PC with keyboard mouse and monitor

OS: WINDOWS10 with pre-installed MVS2pro Density Manager Software




MVS2pro Density System vs the oldest column gradient method




MVS pro system	Gradient column system
Direct measure	Indirect measure of the sample
Easiest certificability of the system	Difficult certificability of the procedure
Integrated Statistical Quality Control Plan	External difficult qualification of the measure
Remote Check and Support of Diagnosis	Not available
Very Fast measure	Very Slow measure
Accuracy, reproducibility and reliability of the measurement	Not available
Result not influenced by the technical skills of the operator"	Result dependent on the technical skills of the operator
Managed Data compliant with the Smart Manufacturing International Plan	Not compliant


Our Density Management Software




Complete setting and calibration of the instrument from the Windows application



Easy and immediate method setting up to 16 samples (including the use of templates)




Fully automated sequence reading, including control tests and correct detection of measured parameters.



Control of all the set up and all the data analysis phases stored in the software database, including the graphs of the data taking in air and liquid.

4.0 Industry



The system can be fully integrated within the company LAN with the ability to transfer analytical data to the areas of competence identified automatically.

On demand services



- Demo in Live Webinar
- In Live measurement of customer's samples



MVS2proDENSITY

Our Partners representative around the World



**Italy, Czech Republic
Austria**

Ortelli Technologies



601 Pistoiese Street
59100 Prato PO
Tel.: +39 0574 668301
www.ortellitechnologies.com
www.ortelli.it
E-Mail: info@ortellitechnologies.com

China

Golden Land Technology



3004, Tower B, U-SPACE,
No.8 Guangqumenwai Avenue
100022 Chaoyang District, Beijing
Tel.: +86 1058613618/58613619/
13910605171
www.goldenlandtech.com
E-Mail: info@goldenlandtech.com

**France, Luxembourg,
french speaking area
of Belgium;
french speaking area
of Switzerland;
french speaking countries
of Africa**

Delta Labo



Bâtiment Le Venango – AGROPARC
392 Rue Jean Dausset - BP 11575
84916 AVIGNON Cédex 9 – France
Tel. : +33 490271795
www.deltalabo.fr
E-Mail: jesus.serra@deltalabo.fr

**United States, Canada
Mexico, Colombia
Brazil**

NTS America Corporation



18 Bridge Street Unit 2A Brooklyn NY 11201
Tel.: +1 (786) 753 7709
www.ntsinter.com
E-Mail: info@ntsinter.com

**Russia, Kazachstan
England, Germany
Spain, Portugal
Albania**

NTS International Group



Via dei Navicellari,6
0122 Roma, RM
www.ntsinternational.com
E-Mail: info@ntsinter.com

India

ABS Instruments Pvt LTD



Unit 21, Block 1, SIDCO electronic
complex,
Thiru Vi Ka Industrial Estate,
Guindy, Chennai - 600032
Phone: +91-44-22500305 / 22500009 /
22500346
www.absinstruments.com
E-Mail: sales@absinstruments.com
NABL accredited calibration lab

Saudi Arabia

Gulf Bio Analytical Group



Office 902, Sapphire Tower
Al Ittihad Rd, near DNATA Deira
Dubai, UAE.
Phone: + 971 4 250 7300
www.gulfbioanalytical.com
E-Mail: contactus@gulfbioanalytical.com



MVS2pro DENSITY

Ortelli Technologies Srl

Via Pistoiese, 601 59100 Prato ITALY

T +39.0574-668301

F +39.0574-811757

www.ortellitechnologies.com

www.ortelli.it

info@ortellitechnologies.com



watch the video
youtu.be/tMWOHqX2eH4



Twitter [/ortellitech](https://twitter.com/ortellitech)



LinkedIn [/company/
ortelli-technologies-s-r-l/](https://www.linkedin.com/company/ortelli-technologies-s-r-l/)



Instagram
[/ortelli_technologies/](https://www.instagram.com/ortelli_technologies/)