

1. PRODUCT INFORMATION

1.1 GENERAL	Professional, washable acrylic water paint for large surfaces.
1.2 PRODUCT IDENTIFICATION	VERNICE MAX
1.3 SUPPLIER	Vernice S.r.l. Via Maccaferri, 2/A; 40069 Zola Predosa (BO), Italia Call center: +39 051 002 2200 E-mail: ciao@vernice.it http://www.vernice.it
1.4 BRANDS & IP OWNER	Vernice S.r.l.
1.5 PRODUCT SPEC DESCRIPTION	Water paint formulated with innovative acrylic resins, ideal for application on Walls, Ceilings and Plasterboard. It is the ideal finish for installation on large surfaces and Contract projects. The revolutionary production technology "VERNICE H2O PAINTS ON DEMAND" allows unlimited color solutions and highly opaque color combinations.
1.6 INTENDED USE	Suitable for interior and exterior use. Ideal for cementitious plasters, plasters and paints based on lime, precast cement, gypsum and scagliola, after careful preparation of the substrate. previously sealed and treated with VERNICE Fixative and VERNICE Primer, if necessary.
1.7 TECHNICAL FEATURES	<p>Data measured at 25°C, U.R. 65%</p> <p>SPECIFIC WEIGHT <i>1600 ± 50 g/L</i></p> <p>PHYSICAL STATUS <i>Viscous liquid</i></p> <p>APPEARANCE <i>Matte</i></p> <p>BINDER TYPE <i>Styrenacrylic</i></p> <p>DRY RESIDUE BY WEIGHT <i>66%</i></p> <p>BROOKFIELD VISCOSITY <i>23.000 cps at 25°C ± 3.000</i></p> <p>APPLICATION <i>Brush, Roller, Spray</i></p> <p>DILUTION <i>30-40% with brush and roller, 25-30% with spray</i></p> <p>YIELD <i>10-12 m²/l per coat depending on surface absorption</i></p> <p>RECOMMENDED NUMBER OF COATS <i>2</i></p> <p>DRYING <i>2 h at 25°C and 65% U.R.</i></p> <p>OVERCOATING <i>4-5 h at 25°C and 65% U.R.</i></p> <p>COLOUR <i>16 mln reproducible colors with RGB VERNICE system</i></p> <p>STORAGE LIFE <i>24 months</i></p> <p>CLEANING TOOLS <i>Water</i></p> <p>Brilliance <i>Very opaque</i></p> <p>UNI EN ISO 2813</p> <p>Wet scrub resistance <i>Class 3</i></p> <p>UNI EN ISO 11998</p> <p>Hiding power <i>Class 3</i></p> <p>Contrast ratio</p> <p>UNI EN ISO 6504-3</p> <p>UNI 8681 CLASSIFICATION <i>Aqueous dispersion, single-component, physically drying, opaque, styrenacrylic finish coat paint. (B4.C.O.A.2.IA)</i></p>
1.8 PACKAGING	10 l

2. APPLICATION

2.1 APPLICATION CONDITIONS	<p>New surfaces: thoroughly clean the surface by brushing and/or washing and apply one coat of VERNICE Fixative.</p> <p>Old surfaces: remove any old paint or unanchored plaster, thoroughly clean the surface of dust and dirt, proceed to apply a coat of VERNICE Fissativo.</p> <p>Surfaces with mold: after cleaning, disinfest with appropriate products and allow to dry perfectly, then proceed to any grouting and application of fixative as described above.</p>
----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<p>2.2 SECURITY AND ENVIRONMENTAL INFORMATION</p>	<p>Hazard-related classification: The product is not classified as hazardous under the provisions of EC Regulation 1272/2008 (CLP) and subsequent amendments and adjustments. Ensure good ventilation during application and drying. When applying paint, wear hand and eye protection. In case of hand contact, remove splashes from the skin using soap and water. In case of eye contact, rinse immediately with plenty of water and consult a doctor. Type of waste: The plastic packaging, if properly reclaimed, could be sent for recovery or recycling as waste bearing EWC code 150102. In any case, local regulations in force should be taken into account.</p>
<p>2.3 STORAGE</p>	<p>Storage and validity: Storage temperature between +5 °C and +30 °C. The product should preferably be used within 24 months from the date of production. Store in the original tightly closed containers and stored in a cool, dry place, away from frost and heat sources.</p>

3. LIMITED WARRANTY

The effectiveness of our products and systems is based on practical experience and research conducted in our laboratories. We guarantee that the quality of work performed with our products, meets the suitability requirements set forth by VERNICE S.R.L., provided that all instructions given by us are properly followed and the work has been properly performed. In the event that the final result has been adversely affected by circumstances beyond our control, any and all liability is expressly excluded and disclaimed. The buyer is responsible for checking whether the delivered products are suitable for the intended use. We reserve the right to change the contents of this document, without prior notice. As soon as a new version of this data sheet becomes available, it will no longer be valid. Please contact our Customer Service for further information. We accept no liability for the performance of the products, resulting from their use beyond the value of the goods supplied by us. This clause does not affect your statutory rights.